

Типоразмер вентилятора	Конструктивное исполнение	D/Dн	Электродвигатель		Частота вращения рабочего колеса, об/мин	Параметры в рабочей зоне		Масса вентилятора, кг	Виброизоляторы	
			типоразмер	мощность, кВт		производительность, 10 <sup>3</sup> м <sup>3</sup> /ч	полное давление, Па		тип	количество
ВЦ4-75-2,5 ВЦ4-75-2,5К1	1	0,95	АИР56А4	0,12	1350	0,3-0,7	180-100	30,0	ДО-38	4
			АИР63А2	0,37	2730	0,7-1,5	790-460	30,0		
			АИР63В2	0,55	2730	0,7-1,7	790-460	30,0		
		1,0	АИР56А4	0,12	1350	0,4-0,8	200-119	30,0		
			АИР63А4	0,25	1320	0,4-0,9	200-128	30,0		
			АИР63В4	0,37	1320	0,45-1,05	210-130	30,0		
			АИР63В2	0,55	2730	0,8-1,7	870-514	30,0		
		1,05	АИР56В4	0,18	1350	0,4-1,0	224-130	30,0		
			АИР63В2	0,55	2730	0,9-2,0	960-560	30,0		
			АИР71А2	0,75	2815	0,9-2,0	960-560	30,0		
			АИР71В2	1,1	2800	0,9-2,0	960-560	30,0		
		ВЦ4-75-3,15 ВЦ4-75-3,15К1	1	0,95	АИР56В4	0,18	1350	0,7-1,5		
АИР71В2	1,1				2800	1,4-3,1	1250-730	34,0		
1,0	АИР56В4			0,18	1350	0,8-1,80	320-180	34,0		
	АИР63А4			0,25	1320	1,18-1,56	570-230	35,0		
	АИР71А4			0,55	1410	1,80-2,30	610-480	38,0		
	АИР71В4			0,75	1415	1,9-2,4	620-490	42,0		
	АИР80А4			1,1	1420	1,9-2,4	620-490	42,0		
	АИР71В2			1,1	2800	1,7-2,8	1390-1200	42,0		
	АИР80А2			1,5	2835	1,7-3,7	1390-810	42,0		
	АИР80В2			2,2	2835	2,3-5,0	1400-840	42,0		
1,05	АИР63А4			0,25	1320	0,9-2,1	350-190	49,0		
	АИР63В4			0,37	1320	0,9-2,1	350-190	49,0		
	АИР80А2			1,5	2835	1,9-4,2	1530-890	49,0		
	АИР80В2			2,2	2820	1,9-4,2	1530-890	49,0		
	АИР90L2			3,0	2835	2,35-5,6	1530-890	51,0		
ВЦ4-75-4	1	0,95	АИР63А6	0,18	860	0,9-2,0	220-130	42,0	ДО-38	4

ВЦ4-75-4К1			АИР71А4	0,55	1410	1,5-3,0	520-340	51,0		4				
			АИР100S2	4,0	2820	2,9-6,0	2075-1000	61,0		5				
		1,0	АИР63А6	0,18	860	1,1-2,3	240-150	42,0		4				
			АИР63В4	0,37	1320	1,5-3,2	570-364	42,0						
			АИР71В6	0,55	1000	1,2-2,57	247-150	51,0						
			АИР71А4	0,55	1410	1,7-3,4	580-375	51,0						
			АИР80А6	0,75	930	1,5-3,5	247-150	53,0						
			АИР90L2	3,0	2835	3,2-7,1	2000-1200	56,0						
			АИР100S2	4,0	2820	3,4-7,0	2300-1200	61,0						
		1,05	АИР63В6	0,25	860	1,3-2,7	260-160	42,0		4				
			АИР71А6	0,37	920	1,3-2,7	260-160	50,0						
			АИР71В4	0,75	1415	2,0-4,1	640-400	51,0						
			АИР80А4	1,1	1420	2,0-4,1	640-400	53,0						
			АИР100L2	5,5	2860	3,9-8,1	2500-1580	63,0						
АИР112М2	7,5		2895	3,9-8,1	2500-1580	82,0								
ВЦ4-75-5 ВЦ4-75-5К1	1	0,95	АИР71В6	0,55	920	2,2-4,5	345-200	74,0	ДО-38	7				
			АИР80В4	1,5	1420	3,4-7,0	820-490	80,0						
		1,0	АИР71В6	0,55	920	2,6-5,3	380-230	74,0						
			АИР80В6	1,1	930	3,0-5,7	390-250	80,0						
			АИР80А4	1,1	1420	3,5-7,2	715-400	78,0						
			АИР80В4	1,5	1420	3,67-7,16	726-382	80,0						
			АИР90L4	2,2	1390	4,0-8,2	910-550	81,0						
		1,05	АИР80А6	0,75	930	3,0-6,1	420-250	78,0						
			АИР90L4	2,2	1390	5,0-9,5	1000-600	86,5						
			АИР100S4	3,0	1395	5,0-9,5	1000-600	95,5						
			АИР100L4	4,0	1425	6,0-12,0	1010-600	104,5						
		ВЦ4-75-6,3 ВЦ4-75-6,3К1	1	0,95	АИР80В6	1,1	930	4,5-9,1			540-320	128,0	ДО-41	4
					АИР90L6	1,5	925	4,5-9,1			540-320	130,0		
					АИР100L6	2,2	925	5,0-11,0			545-320	136,0		
АИР100L4	4,0				1450	6,9-14,1	1300-780	136,0						
АИР112М4	5,5				1450	6,9-14,1	1300-780	157,0						
1,0	АИР80В6			1,1	930	0,49-10,0	600-350	128,0						
	АИР90L6			1,5	925	5,2-10,6	600-360	130,0						

			АИР100L6	2,2	925	5,5-11,0	610-360	136,0		
			АИР112М4	5,5	1450	8,0-16,4	1450-870	157,0		
			АИР132S4	7,5	1455	8,0-16,4	1450-870	173,0		
		1,05	АИР100L6	2,2	925	6,0-12,3	660-390	137,0		
			АИР112М4	5,5	1450	9,0-19,0	1630-970	158,0		
			АИР132S4	7,5	1455	9,3-19,0	1600-950	173,0		
			АИРМ132М4	11,0	1440	9,3-19,0	1600-950	181,0		
		0,95	АИР132S6	5,5	950	7,7-19,0	900-440	231,0		
			АИР112МВ6	4	960	9,0-17,0	800-380	225,0		
			АИРМ132S8	4,0	710	8,4-15,0	540-480	231,0		
			АИР132S6	5,5	950	9,0-22,0	1000-490	231,0		
			АИР132М8	5,5	710	8,7-16,0	550-485	236,0		
			АИР132М6	7,5	960	12,0-23,0	1000-580	236,0		
			АИР160S6	11	970	13,0-24,0	1080-900	300,0		
		1,05	АИР132М6	7,5	960	10,4-25,5	1100-540	236,0		
			АИР160М4	18,5	1460	16,5-32,4	2170-1395	320,0		
ВЦ4-75-8 ВЦ4-75-8К1	1								ДО-41	5
ВЦ4-75-10 ВЦ4-75-10К1	1								ДО-43	4
		0,95	АИР132М8	5,5	730	12,9-27,5	790-410	445,0		
			АИР160S8	7,5	730	12,9-27,5	790-410	482,0		
			АИР160S6	11,0	975	17,4-36,3	1380-730	484,0		
			АИР160М6	15,0	975	17,4-36,3	1380-730	504,0		
			АИР160S8	7,5	730	15,1-32,1	880-460	482,0		
			АИР160М8	11,0	730	15,1-32,1	880-460	502,0		
			АИР160М6	15,0	975	20,3-42,3	1330-810	504,0		
			АИР180М6	18,5	975	20,3-42,3	1330-810	550,0		
			4А200М6	22,0	975	20,3-42,3	1330-810	582,0		
			4А200L6	30,0	975	20,3-42,3	1330-810	582,0		
		1,05	АИР160М8	11,0	735	17,8-37,2	970-550	502,0		
			АИР180М8	15,0	735	17,8-37,2	970-500	550,0		
			АИР180М6	18,5	970	23,5-49,0	1680-890	550,0		
			4А200М6	22,0	970	23,5-49,0	1680-890	582,0		

			4A200L6	30,0	970	23,5-49,0	1680-890	582,0		
ВЦ4-75-12,5 ВЦ4-75-12,5К1	1	0,95	АИР180М8	15,0	735	25,7-40,6	1240-1000	870,6	ДО-43	5
			4A200M8	18,5	735	25,7-53,6	1240-640	906,3		
		1	4A200L8	22,0	735	30,1-62,7	1370-720	921,3		
			4A225M8	30,0	735	30,1-62,7	1370-720	986,3		
		1,05	4A200L8	22,5	735	33,1-45,5	1513-1400	921,39		
			4A225M8	30,0	735	33,1-72,5	1513-790	986,3		